









單色系列(Side-View側光室內型)

Code	Color	CCT(K) λ p(nm)	IC (bulid-in)	Power TYP. (W/M)	Operating Voltage (DC)			TYP. Flux (lm)/5M	CRI	Max. Length L*W*H (cm)	Angle (Deg)	Reference					
					MIN.	TYP.	MAX.					LED Quantity/ M	LED's Source	Min. Length/ Section (cm)	Deliverly (Days)	Water- proof Conector / 5M	Location
VI3616UR /seris		630±5nm	Yes	4	18	24	32	600	----	500*10*0.3	120	60	3014 EPISTAR	10	30	None	Indoor
VI3616UBX /seris		470±5nm	Yes	4				450	----	500*10*0.3		60					
VI3616PGX /seris		525±5nm	Yes	4				1000	----	500*10*0.3		60					
VI3616UYX /seris		592±5nm	Yes	4				600	----	500*10*0.3		60					
VI3608UR /seris		630±5nm	Yes	7.2				1100	----	500*10*0.3		120					
VI3608UBX /seris		470±5nm	Yes	7.2				800	----	500*10*0.3		120					
VI3608PGX /seris		525±5nm	Yes	7.2				1800	----	500*10*0.3		120					
VI3608UYX /seris		592±5nm	Yes	7.2				1100	----	500*10*0.3		120					

Cutting Length is available to fit needs