









單色系列(TOP正面光)半戶外套管IP68

鈺陸光電2021/8/6

Code	Color	CCT(K) λ p(nm)	IC (bulid-in)	Power TYP, (W/M)	Operating Voltage (DC)			TYP. Flux (lm)/5M	CRI	Max. Length L*W*H (cm)	Angle (Deg)	Reference					
					MIN.	TYP.	MAX.					LED Quantity/ M	LED's Source	Min. Length/ Section (cm)	Deliverly (Days)	Water- proof Conector / 5M	Location
I3616URX - H /seris		630±5nm	Yes	4	18	24	32	600	----	500*10*0.5	120	60	3014 EPISTAR	10	30	Available	Semi- Outdoor
I3616UBX - H /seris		470±5nm	Yes	4				450	----	500*10*0.5		60					
I3616PGX - H /seris		525±5nm	Yes	4				1000	----	500*10*0.5		60					
I3616UYX - H /seris		592±5nm	Yes	4				600	----	500*10*0.5		60					
I3608URX - H /seris		630±5nm	Yes	7.2				1100	----	500*10*0.5		120	5	30			
I3608UBX - H /seris		470±5nm	Yes	7.2				800	----	500*10*0.5		120					
I3608PGX - H /seris		525±5nm	Yes	7.2				1800	----	500*10*0.5		120					
I3608UYX - H /seris		592±5nm	Yes	7.2				1100	----	500*10*0.5		120					

Cutting Length is available to fit needs