









5050單色系列(TOP正面光;室內)旗艦款

Code	Color	CCT(K) λ d(nm)	Protecting IC (bulid- in)	Power (W/M)	Operating Voltage (DC)			TYP. Flux (lm)/5M	CRI	Max. Dimension Length L*W*H (cm)	Angle (Deg)	Reference					
					MIN.	TYP.	MAX.					LED Quantity/ M	LED's Source	Min. Length/ Section (cm)	Deliverly (Days)	Water- proof Conector / 5M	Location
5021XAX /seris		592±5nm	Y	10	18	24	32	750	----	500*10*0.03	120	48	5050 EPSTAR	12.5	30	NONE	In-Door
5021XRX /seris		630±5nm	Y	10				800	----	500*10*0.03		48					
5021XBX /seris		470±5nm	Y	10				550	----	500*10*0.03		48					
5021XGX /seris		525±5nm	Y	10				1200	----	500*10*0.03		48					
5016XAX /seris		592±5nm	Y	15				850	----	500*10*0.03		60					
5016XRX /seris		630±5nm	Y	15				900	----	500*10*0.03		60					
5016XBX /seris		470±5nm	Y	15				620	----	500*10*0.03		60					
5016XGX /seris		525±5nm	Y	15				1350	----	500*10*0.03		60					