







# 3014雙色溫系列(TOP正面光)旗艦款(室內型)

Code	Color	CCT(K) λ p(nm)	IC (bulid-in)	Power TYP, (W/M)	Vf(DC) V	TYP. Flux (lm)/5M	CRI	Max. Length L*W*H (cm)	Angle (Deg)	Reference					
										LED Quantity/ M	LED's Source	Min. Length/ Section (cm)	Deliverly (Days)	Water-proof Conector / 5M	Location
BI3605YNWX /seris		3000±150	NONE	15	24	3500	80 ↑	500*1.0*0.3	120	192	3014 PHILIPS	6.25	21	IP20	In-Door
		6000±500				4200	80 ↑								
	4000/Y+N	7500				90									
BI3608OYWX /seris		2200±150	NONE	14	24	2250	80 ↑	500*1.0*0.3	120	120	3014 PHILIPS	10.0	21	IP20	In-Door
		3000±150				3000	80 ↑								
	2700/O+Y	5000				80 ↑									
BI3608OYWX /seris		470nm	NONE	14	24	400	-----	500*0.8*0.3	120	120	3014 PHILIPS+ EPISTAR	10.0	21	IP20	In-Door
		4000±400				1800	80 ↑								
	-----	2000				-----									