









2835RGB系列(TOP正面光)室內旗艦款

Code	Color	CCT(K) λ p(nm)	IC (bulid-in)	Power TYP, (W/M)	Operating Voltage (DC)			TYP. Flux (lm)/5M	CRI	Max. Length L*W*H (cm)	Angle (Deg)	Reference					
					MIN.	TYP.	MAX.					LED Quantity/ M	LED's Source	Min. Length/ Section (cm)	Deliverly (Days)	Water- proof Conector / 5M	Location
I2816UVX /seris		630±5nm	YES	4.5	18	24	32	800	----	500*1.0*0.03	120	60	2835 EPISTAR	10	30	None	In-Door
I2816UBX /seris		470±5nm		3.4				400	----	500*1.0*0.03		60					
I2821PGX /seris		525±5nm		5.3				2500	----	500*1.0*0.03		60					
I2816UYX /seris		592±5nm		4.5				800	----	500*1.0*0.03		60					
I2810UVX /seris		630±5nm		7.8				1250	----	500*1.0*0.03		96		6.25	30		
I2816UBX /seris		470±5nm		7.8				800	----	500*1.0*0.03		96					
I2821PGX /seris		525±5nm		7.8				3300	----	500*1.0*0.03		96					
I2816UYX /seris		592±5nm		7.8				1250	----	500*1.0*0.03		96					