











3014單色系列(TOP正面光)旗艦款(PU戶外IP68)

Code	Color	CCT(K) λ p(nm)	IC (bulid-in)	Power TYP, (W/M)	Operating Voltage (DC)			TYP. Flux (lm)/5M	CRI	Max. Length L*W*H (cm)	Angle (Deg)	Reference					
					MIN.	TYP.	MAX.					LED Quantity/ M	LED's Source	Min. Length/ Section (cm)	Deliverly (Days)	Water- proof Conector / 5M	Location
I3616OWX /seris		2200±150	YES	5	18	24	32	2000	80 ↑	504*1.2*0.5	120	60	3014 PHILIPS	21	IP68	Outdoor	
I3616WWX /seris		2700±150		5				2000	85 ↑	504*1.2*0.5		60					
I3616YWX /seris		3000±150		5				2000	85 ↑	504*1.2*0.5		60					10.0
I3616PWX /seris		4000±400		5				2000	80 ↑	504*1.2*0.5		60					
I3616NWX /seris		5000±500		5				2500	80 ↑	504*1.2*0.5		60					
I3608OWX /seris		2200±150		10				3600	80 ↑	504*1.2*0.5		120					
I3608YWX /seris		3000±150		10				3800	80 ↑	504*1.2*0.5		120					5.0
I3608PWX /seris		4000±400		10				3800	80 ↑	504*1.2*0.5		120					
I3605YWX /seris		3000±150		15				8000	80 ↑	504*1.2*0.5		192					3.125
I3605PWX/4 mm /seris		4000±400		1/0.33				150/0.33 M	87	504*1.2*0.5		200					3.0