











3014單色系列(TOP正面光)旗艦款(半戶外IP68)

| Code | Color | CCT(K) λ p(nm) | IC (bulid-in) | Power TYP, (W/M) | Operating Voltage (DC) | | | TYP. Flux (lm)/5M | CRI | Max. Length L*W*H (cm) | Angle (Deg) | Reference | | | | | |
|-------------------------|---|-------------------|---------------|------------------------|------------------------|------|------|-------------------------|------|------------------------------|----------------|-----------------------|-----------------|------------------------------------|---------------------|-------------------------------------|----------|
| | | | | | MIN. | TYP. | MAX. | | | | | LED Quantity/ M | LED's Source | Min. Length/ Section (cm) | Deliverly (Days) | Water- proof Conector / 5M | Location |
| I3616OWX /seris |  | 2200±150 | YES | 5 | 18 | 24 | 32 | 2000 | 80 ↑ | 504*1.2*0.5 | 120 | 60 | 3014 PHILIPS | 21 | IP68 | Semi- Door | |
| I3616WWX /seris |  | 2700±150 | | 5 | | | | 2000 | 85 ↑ | 504*1.2*0.5 | | 60 | | | | | |
| I3616YWX /seris |  | 3000±150 | | 5 | | | | 2000 | 85 ↑ | 504*1.2*0.5 | | 60 | | | | | 10.0 |
| I3616PWX /seris |  | 4000±400 | | 5 | | | | 2000 | 80 ↑ | 504*1.2*0.5 | | 60 | | | | | |
| I3616NWX /seris |  | 5000±500 | | 5 | | | | 2500 | 80 ↑ | 504*1.2*0.5 | | 60 | | | | | |
| I3608OWX /seris |  | 2200±150 | | 10 | | | | 3600 | 80 ↑ | 504*1.2*0.5 | | 120 | | | | | |
| I3608YWX /seris |  | 3000±150 | | 10 | | | | 3800 | 80 ↑ | 504*1.2*0.5 | | 120 | | | | | 5.0 |
| I3608PWX /seris |  | 4000±400 | | 10 | | | | 3800 | 80 ↑ | 504*1.2*0.5 | | 120 | | | | | |
| I3605YWX /seris |  | 3000±150 | | 15 | | | | 8000 | 80 ↑ | 504*1.2*0.5 | | 192 | | | | | 3.125 |
| I3605PWX/4 mm /seris |  | 4000±400 | | 1/0.33 | | | | 150/0.33 M | 87 | 504*1.2*0.5 | | 200 | | | | | 3.0 |