







# 3014雙色溫系列(TOP正面光)旗艦款(半戶外IP68)

Code	Color	CCT(K) λ p(nm)	IC (bulid-in)	Power TYP, (W/M)	Vf(DC) V	TYP. Flux (lm)/5M	CRI	Max. Length L*W*H (cm)	Angle (Deg)	Reference											
										LED Quantity/ M	LED's Source	Min. Length/ Section (cm)	Deliverly (Days)	Water-proof Conector / 5M	Location						
BI3605YNWX /seris		3000±150	NONE	15	24	3500	80 ↑	504*1.2*0.5	120	192	3014 PHILIPS	6.25	21	IP68	Semi- Outdoor						
		6000±500				4200	80 ↑														
		4000/Y+N				7500	80 ↑														
BI3608OYWX /seris		2200±150		14		14	2250	80 ↑		504*1.2*0.5		120				120	3014 PHILIPS+ EPISTAR	10.0	21	IP68	Semi- Outdoor
		3000±150					3000	80 ↑													
		2700/O+Y					5000	80 ↑													
BI3608OYWX /seris		470nm	14	14	400	----	504*1.2*0.5	120	120	3014 PHILIPS+ EPISTAR	10.0		21	IP68	Semi- Outdoor						
		4000±400			1800	80 ↑															
		-----			2000	----															