












2835單色系列(TOP正面光)半戶外套管IP68經濟款

Code	Color	CCT(K) λ p(nm)	IC (bulid-in)	Power TYP, (W/M)	Vf(DC) V	TYP. Flux (lm)/5M	CRI	Max. Length L*W*H (cm)	Angle (Deg)	Reference					
										LED Quantity/ M	LED's Source	Min. Length/ Section (cm)	Deliverly (Days)	Water-proof Conector / 5M	Location
V2810YWX-H /seris		3000±150		7	12	5500	80	504*1.2*0.03	120	96	2835 EPISTAR	3.12	30	Available	Semi- Outdoor
V2810PWX-H /seris		4000±400		7		5500	80	504*1.2*0.03		96					
V2810NWX-H /seris		6000±500		7		5500	80	504*1.2*0.03		96					
V2816YWX-H /seris		3000±150		5		2800	80	504*1.0*0.03		60					
V2816PWX-H /seris		4000±400		5		2800	80	504*1.0*0.03		60					
V2816NWX-H /seris		6000±500		5		2800	80	504*1.0*0.03		60					
V2808YWX-H /seris		3000±150	None	10	24	6000	80	504*1.0*0.03	120	120	2835 EPISTAR	5	30	Available	Semi- Outdoor
V2808PWX-H /seris		4000±400	10	6000		80	504*1.0*0.03	120							
V2808NWX-H /seris		6000±500	10	6000		80	504*1.0*0.03	120							
V2816WWX-H /seris		2700±150		5	24	2800	80	504*1.0*0.03	120	60	2835 EPISTAR	10	30	Available	Semi- Outdoor
V2816YWX-H /seris		3000±150		5		2800	90	504*1.0*0.03		60					

