




















2835單色系列(TOP正面光)室內經濟型

Code	Color	CCT(K) λ p(nm)	IC (bulid-in)	Power TYP, (W/M)	Vf(DC) V	TYP. Flux (lm)/5M	CRI	Max. Length L*W*H (cm)	Angle (Deg)	Reference						
										LED Quantity/M	LED's Source	Min. Length/Section (cm)	Deliverly (Days)	Water-proof Conector / 5M	Location	
V2810YWX /seris		3000±150		7	12	5500	80	500*1.0*0.03		96						
V2810PWX /seris		4000±400		7		5500	80	500*1.0*0.03		96						3.12
V2810NWX /seris		6000±500		7		5500	80	500*1.0*0.03		96						
V2816YWX /seris		3000±150		5		2800	80	500*0.8*0.03		60						
V2816PWX /seris		4000±400		5		2800	80	500*0.8*0.03		60						5
V2816NWX /seris		6000±500		5		2800	80	500*0.8*0.03		60						
V2807YWX /seris		3000±150		7.2		6600	80	500*0.8*0.03		140						
V2807PWX /seris		4000±400		7.2		6600	80	500*0.8*0.03		140						
V2807NWX /seris		6000±500		7.2		6600	80	500*0.8*0.03		140						
V2807YWX /seris		3000±150		None		12	6600	80		500*1.2*0.03						120

V2807PWX /seris		4000±400		12		6600	80	500*1.2*0.03		140				
V2807NWX /seris		6000±500		12		6600	80	500*1.2*0.03		140				
V2808YWX /seris		3000±150		10	24	6000	80	500*0.8*0.03		120				
V2808PWX /seris		4000±400		10		6000	80	500*0.8*0.03		120		5		
V2808NWX /seris		6000±500		10		6000	80	500*0.8*0.03		120				
V2816WWX /seris		2700±150		5		2800	80	500*0.8*0.03		60				
V2816YWX /seris		3000±150		5		2800	90	500*0.8*0.03		60			10	
V2816PWX /seris		4000±400		5		2800	90	500*0.8*0.03		60				
V2816NWX /seris		6000±500		5		2800	80	500*0.8*0.03		60				