














2835單色系列(TOP正面光)戶外全天候灌膠IP68經濟款

鈺陸光電2021/8/6

Code	Color	CCT(K) λ p(nm)	IC (bulid-in)	Power TYP, (W/M)	Vf(DC) V	TYP. Flux (lm)/5M	CRI	Max. Length L*W*H (cm)	Angle (Deg)	Reference					
										LED Quantity/ M	LED's Source	Min. Length/ Section (cm)	Deliverly (Days)	Water-proof Conector / 5M	Location
V2810YWX-PU/seris		3300±150	None	7	12	5000	80	504*1.2*0.03	120	96	2835 EPISTAR	3.12	30	Available	Outdoor
V2810PWX-PU /seris		4000±400		7		5000	80	504*1.2*0.03		96					
V2810NWX-PU/seris		6500±500		7		5000	80	504*1.2*0.03		96					
V2816YWX-PU /seris		3300±150		5		2800	80	504*1.0*0.03		60					
V2816PWX-PU /seris		4000±400		5		2800	80	504*1.0*0.03		60					
V2816NWX-PU /seris		6500±500		5		2800	80	504*1.0*0.03		60					
V2808YWX-PU /seris		3300±150		10		5500	80	504*1.0*0.03		120					
V2808PWX-PU /seris		4000±400		10		5500	80	504*1.0*0.03		120					
V2808NWX-PU /seris		6500±500		10		5500	80	504*1.0*0.03		120					
V2816WWX-PU /seris		2700±150	5	24	2800	80	504*1.0*0.03	60							

V2816YWX- PU /seris		3300±150	5	2800	90	504*1.0*0.03	60	10					
V2816PWX- PU /seris		4000±400	5	2800	90	504*1.0*0.03	60						
V2816NWX- PU /seris		6500±500	5	2800	80	504*1.0*0.03	60						

Cutting Length is available to fit needs