











日亞757單色系列(TOP正面光;)旗艦款;半戶外

Code	Color	CCT(K) λ p(nm)	Protecting IC (bulid- in)	Power TYP, (W/M)	Operating Voltage (DC)			TYP. Flux (lm)/5M	CRI	Max. Length L*W*H (cm)	Angle (Deg)	Reference					
					MIN.	TYP.	MAX.					LED Quantity/ M	LED's Source	Min. Length/ Section (cm)	Deliverly (Days)	Water- proof Conector / 5M	Location
I7521OWX /H seris		2200±150	YES	10	18	24	32	4600	80 ↑	504*1.2*0.5	120	48	3030 NICHIA	45	Available IP68	Semi- Outdoor	
I7521WWX /H seris		2700±150		10				4800	80 ↑	504*1.2*0.5		48					
I7521YWX /H seris		3000±150		10				4800	80 ↑	504*1.2*0.5		48					12.5
I7521PWX /H seris		4000±400		10				4800	80 ↑	504*1.2*0.5		48					
I7521NWX /H seris		5000±500		10				4800	80 ↑	504*1.2*0.5		48					
I7516OWX /H seris		2200±150		12.5				5600	80 ↑	504*1.2*0.5		60					
I7516WWX /H seris		2700±150		12.5				5600	80 ↑	504*1.2*0.5		60					
I7516YWX /H seris		3000±150		12.5				5600	80 ↑	504*1.2*0.5		60					10.0
I7516PWX /H seris		4000±400		12.5				6000	80 ↑	504*1.2*0.5		60					
I7516NWX /H seris		5000±500		12.5				6500	80 ↑	504*1.2*0.5		60					