











日亞757單色系列(TOP正面光;室內)旗艦款

鈺陸光電2021/8/6

Code	Color	CCT(K) λ p(nm)	Protecting IC (bulid- in)	Power TYP, (W/M)	Operating Voltage (DC)			TYP. Flux (lm)/5M	CRI	Max. Length L*W*H (cm)	Angle (Deg)	Reference					
					MIN.	TYP.	MAX.					LED Quantity/ M	LED's Source	Min. Length/ Section (cm)	Deliverly (Days)	Water- proof Conector / 5M	Location
I7521OWX /seris		2200±150	YES	10	18	24	32	4600	80 ↑	500*1.0*0.3	120	48	3030 NICHIA	45	None	In-Door	
I7521WWX /seris		2700±150		10				4800	80 ↑	500*1.0*0.3		48					
I7521YWX /seris		3000±150		10				4800	80 ↑	500*1.0*0.3		48					12.5
I7521PWX /seris		4000±400		10				4800	80 ↑	500*1.0*0.3		48					
I7521NWX /seris		5000±500		10				4800	80 ↑	500*1.0*0.3		48					
I7516OWX /seris		2200±150		12.5				5600	80 ↑	500*1.0*0.3		60					
I7516WWX /seris		2700±150		12.5				5600	80 ↑	500*1.0*0.3		60					
I7516YWX /seris		3000±150		12.5				5600	80 ↑	500*1.0*0.3		60					10.0
I7516PWX /seris		4000±400		12.5				6000	80 ↑	500*1.0*0.3		60					
I7516NWX /seris		5000±500		12.5				6500	80 ↑	500*1.0*0.3		60					