

RGB控制器

鈺陞光電2021/8/6

Code	Input-Voltage (V)	Common Cathode/ Anode	Output(A) (maximum)	(C t) Exchange	Dimmer	Power-Consumption (W)	Remote-Control	WI-FI	Max. Dimension Length L*W*H (mm)	Water-Proof	Note
FW-304	12~24	CA	12.0 / 3CH / RGB	-----	Y	288	Y	Y	108*65*28	N	9 Varity color-exchange available
FL-06	12~24	CA	12.0 / 3CH / RGB	-----	Y	288	Y	N	130*64*24	N	21 Varity color-exchange available
SZ-100	12~24	CA	18.0 / 3CH / RGB	-----	Y	430	Y	N	127*42*33	N	Unlimited Varity color-exchange available
HC-125RGB	12~24	CA	18.0 / 3CH / RGB	-----	Y	-----	Y	N	127*42*33	N	Unlimited Varity color-exchange available
HC-308RGB/S	12~24	CA	18.0 / 3CH / RGB	-----	Y	-----	Y	N	92*90*25	N	Synchronization
NGC-DLV003	12~24	CA	24 / 4CH / RGBW	-----	Multi-Function	576	Y	N	160*46*25	N	Dimmer Biocolor RGB RGBW



HC308/RGB/S

HC308RGB

HC125RGB

SZ100